


SURFACE MOUNT ALUMINUM ELECTROLYTIC CAPACITORS

RC Chip type, Wide Temperature Range Series

- Wide operating temperature range of -55 ~ +105°C
- Designed for surface mounting on high density PC board
- Applicable to automatic insertion machine using carrier tape
- Complied to the RoHS directive
- AEC-Q200 compliant : Please contact us for more details.



Item	Characteristics							
Operating temperature range	-55 ~ +105°C							
Leakage current max.	I = 0.01CV or 3μA whichever is greater (after 2 minutes)							
Capacitance tolerance	±20% at 120Hz, 20°C							
Dissipation factor max. (at 120Hz, 20°C)	WV	6.3	10	16	25	35	50	
	tanδ	0.27	0.23	0.19	0.15	0.13	0.11	
Low temperature characteristics (Impedance ratio at 120Hz)	WV		6.3	10	16	25	35	50
	Z-25°C/Z+20°C		3	3	2	2	2	2
	Z-55°C/Z+20°C		8	5	4	3	3	3
Load life (after application of the rated voltage for 1000 hours at 105°C)	Leakage current			Less than specified value				
	Capacitance change			Within ±25% of initial value				
	tanδ			Less than 200% of specified value				
Shelf life (at 105°C)	After 1000 hours no load test, leakage current, capacitance and tanδ are same as load life value. The measurement shall be performed at 20°C by the KS C IEC 60384 - 4							
Resistance to soldering heat	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them at 250°C for 10 seconds.							
	Leakage current			Less than specified value				
	Capacitance change			Within ±10% of initial value				
	tanδ			Less than specified value				

● DRAWING (See page 56)

-Series code of RC is "F"

● DIMENSIONS & MAXIMUM PERMISSIBLE RIPPLE CURRENT

μF \ WV	6.3		10		16		25		35		50	
1.0											4×5.3	7
2.2											4×5.3	11
3.3											4×5.3	13
4.7							4×5.3	13	4×5.3	14	5×5.3	18
10					4×5.3	17	5×5.3	23	5×5.3	24	6.3×5.3	31
22	4×5.3	22	5×5.3	27	5×5.3	30	6.3×5.3	39	6.3×5.3	42	6.3×5.8	45
33	5×5.3	31	5×5.3	33	6.3×5.3	43	6.3×5.3	48	6.3×5.8	52	6.3×7.7	60
47	5×5.3	36	6.3×5.3	46	6.3×5.3	51	6.3×5.8	59	6.3×5.8	63	6.3×7.7	63
100	6.3×5.3	50	6.3×5.8	64	6.3×5.8	64	6.3×7.7	91	8×10	296	10×10	295
220	6.3×7.7	86	6.3×7.7	105	6.3×7.7	105	8×10	340	10×10	435		
330	6.3×7.7	105	8×10	305	8×10	340	10×10	360				
470	8×10	330	10×10	340	10×10	470						
1000	10×10	475										

Ripple current (mA rms) at 105°C, 120Hz
 Case size $\varnothing D \times L$ (mm)

● FREQUENCY COEFFICIENT OF PERMISSIBLE RIPPLE CURRENT

Frequency	50Hz	120Hz	300Hz	1kHz	10kHz $\leq$
Coefficient	0.70	1.00	1.17	1.36	1.50